

LENNOX
Innovation never felt so good.®

relaxing warmth



GSB8-E

Standard-
efficiency,
gas-fired
steam boiler

Worry-free performance lets you relax in comfort.

Winter weather can be unpredictable, but you can always count on the Lennox® GSB8-E boiler to deliver solid value and superb heating throughout the season. It's constructed of high-quality materials, including titanium burners and a cast iron heat exchanger that quietly and efficiently supplies steam to your home's radiator system for cozy, comfortable warmth.

Energy savings you'll really warm up to

The GSB8-E offers significant energy savings compared to an older boiler, with efficiency ratings of up to 82.7% AFUE. That means you can enjoy lower utility bills throughout the winter, without sacrificing a degree of comfort.

Put to the test before it even leaves the factory

We fire-test and inspect every unit prior to shipping to ensure the highest possible degree of operating reliability. A 12-year limited warranty on the heat exchanger and a 1-year limited warranty on covered parts** provide additional peace of mind.

Incredible versatility that's always a perfect fit

Available in seven different sizes to fit your home's unique needs, the GSB8-E integrates easily with your existing radiator or underfloor heating system. Plus, options of natural or LP gas* give you more flexibility in how you heat your home.

Quality engineering for years of reliable comfort

Each feature of the GSB8-E boiler is designed to provide season after season of quiet, efficient warmth.

- **Electronic Ignition** – Burns fuel only as necessary, reducing energy costs.
- **Vent Damper** – Automatically closes when the boiler turns off to maintain energy efficiency.
- **Large Steam Chest & Multiple Supply Connections** – Help eliminate the loud “hammering” noise common with other gas-fired steam boilers.
- **Cast Iron Heat Exchanger** – Designed for years of long-lasting reliability over a range of water flow rates.
- **Electronic Low Water Cut Off** – Eliminates homeowner maintenance and helps ensure safe, reliable operation.
- **Thick Fiberglass Insulation** – Minimizes heat and energy loss when the heat exchanger cools down after a cycle.
- **Titanium Burners** – Provide greater resistance to corrosion and oxidation than competitive stainless or aluminized steel burners.

*Shipped as natural gas. Convertible to LP.

**Applies to residential applications only. See actual warranty certificate for details.

GSB8-E Specifications

Model	GSB8-075E	GSB8-112E	GSB8-150E	GSB8-187E	GSB8-225E	GSB8-262E	GSB8-299E
Heating Efficiency (AFUE)	82.7%	80.4%	80.6%	80.9%	81.1%	81.3%	81.5%
Dimensions HxWxD (in) HxWxD (mm)	36-3/8 x 11-1/4 x 26-1/2 924 x 286 x 673	36-3/8 x 14-1/2 x 26-1/2 924 x 368 x 673	36-3/8 x 17-3/4 x 26-1/2 924 x 451 x 673	36-3/8 x 21 x 26-1/2 924 x 533 x 673	36-3/8 x 24-1/4 x 26-1/2 924 x 616 x 673	36-3/8 x 27-1/2 x 26-1/2 924 x 699 x 673	36-3/8 x 30-3/4 x 26-1/2 924 x 781 x 673

Note: Due to Lennox' ongoing commitment to quality, all specifications, ratings and dimensions are subject to change without notice.



For a complete list of the registered and common law trademarks owned by Lennox Industries Inc., please visit www.lennox.com.